

SILENT DIESEL GENERATOR



CONTROL PANEL



- Key start
- Voltmeter
- Hourmeter
- MCB Breaker
- Safety Twisted Lock Socket

DENKO® KDE6500T / KDE6500T3

• Frequency Hz:	50 60	50 60
• Max AC output kw:	5.5 6.0	6.0 6.5
• Rated AC output kw:	5 5.5	5.5 6.0
• DC output V-A:	12/8.3	—
• Rated voltage V:	230/115 240/120	400/230 416/230
• Power factor(cos Φ) :	1.0	0.8
• Phase:	Single-phase	Three-phase
• Voltage Regulator	AVR	AVR
• Dimensions(L×W×H)mm:	910 × 520 × 740	910 × 520 × 740
• Dry weight (kg):	171	171
• Engine:	Air cooled diesel	Air cooled diesel
• Model:	186 FAG	186 FAG
• Type:	Single-cylinder, Vertical,4-stroke,	Single-cylinder, Vertical,4-stroke,
• Displacement cc:	418	418
• Rated output ps/rpm:	8.84/3600	8.84/3600
• Fuel tank capacity:	15	15
• Lube oil capacity:	1.65	1.65
• Operating hours: (Based on 50% load)	12 hours	12 hours